



Testirano i certificirano

- CO₂-Propusnost (DIN EN 1062-6)
- Svojstva sunčeve refleksije, ("Solar Reflectance Index")
- CE-Certifikat (EN 1504-2)



KÖSTER

KÖSTER Vama na usluzi – širom svijeta



// Kontakt

BAUCHEMIE d.o.o.
 Stupničke šipkovine 3/1
 10255 Donji Stupnik
 Tel.: +385 (0)1 6414 051
 E-Mail: info@koster.hr
www.koster.hr

Pratite nas na društvenim mrežama:



Vrijedi od: 4/2023

KÖSTER

Hidroizolacijski sustavi

KÖSTER 21

Univerzalno primjenjiva tekuća hidroizolacija



Visokoreflektirajući

UV-otporan

Načini primjene

- Unutarnja i vanjska primjena
- Hidroizolacija podruma
- Hidroizolacija krovova
- Hidroizolacija ispod pločica
- Balkoni i terase
- Hidroizolacija spremnika i bazena
- Inhibicija karbonizacije
- Sanacija stare bitumenske hidroizolacije

// Primjena



1 Priprema podloge



2 Ugradnja holkera sa KÖSTER Reparturnim mortom



3 Prvi sloj sa KÖSTER 21



4 KÖSTER Superflis se nanosi na prvi svježi sloj



5 Drugi sloj sa KÖSTER 21



6 Završni rezultat



Nanošenje četkom



Nanošenje valjkom



Nanošenje raspršivačem



Nanošenje lopaticom

Glavne karakteristike KÖSTER 21

- Elastičan i za premoščivanje pukotina
- Za unutarnju i vanjsku primjenu
- Otporan na UV zračenja
- Otporan na soli
- Otporan na hidrolizu i učinke smrzavanja / odmrzavanja
- Dobro prianjanje na blago vlažne mineralne podloge
- Dobro prianjanje npr. na beton, metal, PVC ili staru bitumensku hidroizolaciju
- Lako se nanosi
- Otporan na vodu pod pritiskom
- Hidrofoban (učinak odbijanja vode)
- Bez otapala i hlapivih organskih spojeva (VOC)
- Ne sadrži izocijanate i bitumen
- 2-komponentni, brzo stvrdnjavajući
- Bijele boje, reflektira toplinsko zračenje (štedi energiju)
- Svestrano nanošenje: četkom, lopaticom, valjkom ili prskanjem

